

**भारतीय मानक**  
**Indian Standard**

**IS 3581 : 2019**

---

---

**हरी कॉफ़ी — विशिष्टि**

( तीसरा पुनरीक्षण )

**Green Coffee — Specification**

( *Third Revision* )

ICS 67.140.20

© BIS 2019



भारतीय मानक ब्यूरो  
BUREAU OF INDIAN STANDARDS  
मानक भवन, 9 बहादुरशाह ज़फर मार्ग, नई दिल्ली – 110002  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI-110002  
[www.bis.gov.in](http://www.bis.gov.in) [www.standardsbis.in](http://www.standardsbis.in)

October 2019

Price Group 6

Stimulant Foods Sectional Committee, FAD 06

## FOREWORD

This Indian Standard (Third Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Stimulant Foods Sectional Committee had been approved by the Food and Agriculture Division Council.

This standard was first published in 1966 and subsequently revised in 1974 and 1982. The first revision of this standard was brought out to include determination of moisture content with a view to aligning it with the practical method adopted by the ISO. The second revision of the standard was carried out to reflect the latest trade practices followed by the Coffee Board with respect to grade designations.

A scheme for labelling environment friendly products with the ECO Mark was introduced at the instance of the Ministry of Environment and Forests (MoEF), Government of India. The ECO Mark would be administered by the Bureau of Indian Standards (BIS) under the *Bureau of Indian Standards Act, 2016* as per the Resolution No. 71 dated 20 February 1991 as published in the Gazette of the Government of India vide GSR No. 85(E) dated 21 February 1991. For a product to be eligible for ECO Mark it shall also carry the Standard Mark of BIS for quality besides meeting additional optional environmental friendly (EF) requirements. The EF requirements for grading of green coffee, are, therefore being included through an Amendment No. 1 to this standard. Amendment No. 1 was based on the Gazette Notification No. 678 (E) dated 30 August 1994 for Labelling Edible Oils, Tea and Coffee as environment friendly products, published by the Ministry of Environment and Forests.

The third revision is being carried out to incorporate the new grades of coffee introduced by the Coffee Board which are popular in both domestic and international trade along with the incorporation of Eco mark requirements issued via amendments.

In the formulation of this standard, due consideration has been given to the provisions of the *Food Safety and Standards Act, 2006* and the Rules framed thereunder and the *Legal Metrology (Packaged Commodities) Rules, 2011*. However, this standard is subject to the restrictions imposed under these, wherever applicable.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

# Indian Standard

## GREEN COFFEE — SPECIFICATION

( Third Revision )

### 1 SCOPE

This standard prescribes the requirements for different types and grades of green coffee, namely, *Coffea arabica* Linn. and *Coffea caenophora* (subvariety *C. robusta* Linden ).

### 2 TERMINOLOGY

For the purpose of this standard, the following definitions shall apply.

**2.1 Plantation Triage** — Broken, withered, spotted, elephant, small discoloured malformed beans, pales and pulper-cuts.

**2.2 Robusta Parchment and Cherry Triage** — Round small beans, spotted beans, dried and shrivelled beans, broken beans (not less than one-third of a bean in size). In the case of Robusta parchment triage, pales and pulper-cuts are also included.

**2.3 Bits** — Broken coffee of less than one third of a bean in size.

**2.4 Blacks** — More than a quarter of bean surface black, blue, brown or similarly discoloured beans and including stinkers and sour beans.

### 3 VARIETIES AND TYPES

**3.1** There are mainly two varieties of coffee as given below:

- a) Variety I — *Coffea arabica* Linn, and
- b) Variety II — *Coffea caenophora* (subvariety *C. robusta* Linden).

**3.2** There shall be six types of coffee as given below:

- a) Arabica Plantation (washed);
- b) Arabica Cherry (unwashed);
- c) Robusta Parchment (washed);
- d) Robusta Cherry (unwashed);
- e) Mysore Nuggets EB;
- f) Robusta Kaapi Royale; and
- g) Monsooned Malabar Coffees (see IS 4074).

### 4 REQUIREMENTS

#### 4.1 Moisture Content

When determined by the method prescribed in Annex A, the moisture content in coffee at the time of packing shall be as given in Table 1.

**Table 1 Moisture Content in Coffee**  
( Clause 4.1 )

SI No.	Types of Coffee	Moisture Content (Percent)
(1)	(2)	(3)
i)	Arabica, Plantation (washed)	10.5
ii)	Arabica Cherry (unwashed)	11.5
iii)	Robusta Parchment (washed)	10.5
iv)	Robusta Cherry (unwashed)	11.5
v)	Mysore Nuggets EB	9.0-10.5
vi)	Robusta Kaapi Royale	9.0-10.5
vii)	Monsooned Malabar Coffees	13.0-14.5

NOTES:

- 1 A tolerance of + 0.5 percent in moisture content is permissible.
- 2 Moisture standards for the premium grades will be the same as those of the type to which they belong.
- 3 Please refer to the glossary appended at the end for definitions of coffee terms.

#### 4.2 Aperture Size of Test Sieves Used in Coffee and Their Corresponding Screen Number (see Table 2)

**Table 2 Aperture Size of Test Sieves Used in Coffee and their Screen Number**  
( Clause 4.2 )

SI No.	Aperture Size (Diameter of Round Holes in mm)	Screen No.
i)	7.50	19
ii)	7.25	Between 19 and 18
iii)	7.10	18
iv)	6.70/6.65	17
v)	6.50	Between 17 and 16
vi)	6.30	16
vii)	6.00	15
viii)	5.60/5.50	14
ix)	5.00	13

## IS 3581 : 2019

### 4.3 Freedom from Infestation

Coffee beans shall be free from infestation due to insects, fungi and rodents.

### 4.4 Freedom from Extraneous Matter

Coffee beans shall be free from any extraneous matter, such as strings, stones, dirt, wood and glass, and metallic pieces.

### 4.5 Odour

Coffee beans shall be free from any foreign odour.

### 4.6 Requirements for ECO Mark

#### 4.6.1 General Requirements

**4.6.1.1** The product shall conform to the quality standards of Bureau of Indian Standards.

**4.6.1.2** The product manufacturer shall produce the consent clearance as per the provisions of *Water (Prevention and Control of Pollution) Act, 1974* and *Air (Prevention and Control of Pollution) Act, 1981*, *Water (Prevention and Control of Pollution) Cess Act, 1977* respectively along with the authorisation if required, under *Environment (Protection) Act, 1986* and the Rules made thereunder to Bureau of Indian Standards while applying for the ECO Mark; and the product shall be in accordance with the *Prevention of Food Adulteration Act, 1954* and the Rules made thereunder unless otherwise specified.

**4.6.1.3** The product/packing shall display in brief the criteria based on which the product has been labelled environment friendly.

**4.6.1.4** The material used for product/packaging shall be recyclable (that is, which can be reprocessed to manufacture any other useful product) or biodegradable and the parameters evolved under the SLEFP on the specific subject of packaging shall apply.

#### 4.6.2 Specific Requirements

**4.6.2.1** The coffee beans shall be free from infestation due to insects, fungus and rodents.

**4.6.2.2** The product shall be free from extraneous matter like strings, stones, dirt, wood, glass and metallic pieces and from any added colouring and flavouring. It shall also be free from rancidity and shall have its characteristic flavour.

**4.6.2.3** The product shall be free from adulterants like dandelion and other roots, nerons, figs, dates, stones and cereals.

**4.6.2.4** The pesticides residues (if any) in the product shall not exceed the limits as prescribed in

*Food Safety and Standards (Contaminants, Toxins and Residues) Regulations, 2011*, when tested by the methods given in the relevant Indian Standards specifications.

## 5 GRADING AND GARBLING (SORTING) OF GREEN COFFEE

Grading and garbling of Indian coffee is based on the size of the coffee beans and percentage of imperfections. In the Indian system of grading and garbling, the tolerance level for each and every grade is specified and expressed in percentage by weight. Quality specifications for Indian coffee entail that all the grades be totally free from foreign and extraneous matters.

**5.1** There shall be four broadly categorized grades of the washed and unwashed Arabicas and Robustas as given below:

- a) Commercial grades;
- b) Premium grades;
- c) Specialty coffees; and
- d) Miscellaneous grades.

**5.2** Coffee beans shall be graded on the basis of size and shape before packing.

**5.3** The designation of grades and their requirements shall be as given in **5.3.1** to **5.3.4**.

#### 5.3.1 Commercial Grade

- a) Arabica coffee.
  - 1) Washed Arabica 'Plantation' — The grade designations of Arabica plantation coffee are:
    - i) Plantation PB;
    - ii) Plantation A;
    - iii) Plantation B
    - iv) Plantation C;
    - v) Plantation blacks;
    - vi) Plantation bits; and
    - vii) Plantation bulk.

### Quality Specifications

<b>1. Plantation PB</b>	
Sieve standard	No sieve requirement
Garbling status	Clean garbled
Tolerance	
Flats (AB)	2 percent by weight
PB triage	3 percent by weight

- 2. Plantation A**
- Sieve standard Minimum 90 percent by weight retention on a sieve with round holes of 6.65 mm (screen 17). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 6.00 mm (screen 15).
- Garbling status Clean garbled
- Tolerance
- PB 2 percent by weight
- Triage 2 percent by weight
- 3. Plantation B**
- Sieve standard Minimum 75 percent by weight retention on a sieve with round holes of 6.00 mm (screen 15). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 5.50 mm (screen 14).
- Garbling status Clean garbled
- Tolerance
- PB 2 percent by weight
- Triage 3 percent by weight
- 4. Plantation C**
- Sieve standard Minimum 75 percent by weight retention on a sieve with round holes of 5.50 mm (screen 14). 100 percent by weight shall stand on a sieve with round holes of 5.00 mm (screen 13).
- May include Triage, small whole beans of the prescribed sieve size, light beans, boat-shaped beans and spotted beans (less than quarter of a bean surface).
- Shall be free from Blacks and damaged beans.
- 5. Plantation Blacks**
- Sieve standard 100 percent by weight retention on a sieve with round holes of 5.00 mm (screen 13).
- May include Black beans with more than a quarter of the bean surface black, deep blue or dark brown. It shall include damaged beans such as bleached (spongy) beans, insect-damaged beans, spotted (more than a quarter of a bean surface) beans, stinker and sour beans.
- 6. Plantation Bits**
- Sieve standard 100 percent by weight shall pass through a sieve with round holes of 5.00 mm (screen 13).
- Garbling status Un-garbled
- May contain Broken beans of less than 1/3 of a bean size, blacks/Browns and defective beans of the prescribed size.
- May include Triage, small whole beans of the prescribed sieve size, light beans, boat shaped beans and spotted beans (less than a quarter of a bean surface). It shall not contain more than 2 percent of blacks/browns or bits.
- 7. Plantation Bulk**
- Grading Ungraded
- Presence of blacks/Browns/ bits Shall not contain more than 2 percent by weight
- 2) *Unwashed Arabica- 'Arabica Cherry'* — The grade designations of Arabica Cherry coffees are:
- i) Arabica cherry PB;
  - ii) Arabica cherry AB;
  - iii) Arabica cherry C;
  - iv) Arabica cherry blacks/ browns;

**IS 3581 : 2019**

- v) Arabica cherry bits; and
- vi) Arabica cherry bulk.

**Quality Specifications**

**1. Arabica Cherry PB**

Sieve standard	No sieve requirement
Garbling status	Clean garbled
Tolerance	
Flats (AB)	2 percent by weight
PB triage	3 percent by weight

**2. Arabica Cherry AB**

Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.00111m (Screen 15). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 5.50mm (Screen 14).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	3 percent by weight

**3. Arabica Cherry C**

Sieve standard	Minimum 75 percent by weight retention on a sieve with round holes of 5.50mm (screen 14). 100 percent by weight shall stand on a sieve with round holes or 5.00 mm (screen 13).
----------------	---

**4. Arabica Cherry Blacks/Browns**

Sieve standard	100 percent by weight retention on a sieve with round holes of 5.00 mm (screen 13).
May include	Black/dark brown beans, damaged beans such as bleached (spongy) beans, insect-damaged beans, spotted (more than a quarter of a bean surface) beans, fungal-damaged beans, sour and greens.

**5. Arabica Cherry Bits**

Sieve Standard	100 percent by weight shall pass through a sieve with round holes of 5.00 mm (screen 13).
Garbling Status	Un-garbled
May contain	Broken beans of less than 1/3 of a bean size, blacks/Browns and defective beans of the prescribed size.

**6. Arabica Cherry Bulk**

Grading	Ungraded
Presence of blacks/browns/bits	Shall not contain more than 10 percent by weight.

b) Robusta coffee

- 1) *Washed Robusta 'Robusta Parchment'* — The grade designations of Robusta Parchment coffees are:
  - i) Robusta parchment PB;
  - ii) Robusta parchment AB;
  - iii) Robusta parchment C;
  - iv) Robusta parchment blacks/browns;
  - v) Robusta parchment bits; and
  - vi) Robusta parchment bulk .

**Quality Specifications**

**1. Robusta Parchment PB**

Sieve standard	No sieve requirement
Garbling status	Clean garbled
Tolerance	
Flats (AB)	2 percent by weight
PB triage	3 percent by weight

**2. Robusta Parchment AB**

Sieve Standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.00 mm (screen 15). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 5.50 mm (screen 14)
----------------	---

Garbling Status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	3 percent by weight
<b>3. Robusta Parchment C</b>	
Sieve standard	Minimum 75 percent by weight retention on a sieve with round holes of 5.50 mm (screen 14). 100 percent by weight shall be retained on a sieve with round holes of 5.00 mm (screen 13).
May include	Triage, small whole beans of the prescribed sieve size, light beans, boat-shaped beans and spotted beans (less than a quarter of a bean surface). It shall not contain more than 2 percent of blacks/browns or bits.
<b>4. Robusta Parchment blacks/browns</b>	
Sieve standard	100 percent by weight retention on a sieve with round holes of 5.00 mm (screen 13).
May include	Blacks/dark brown beans, damaged beans, such as bleached (spongy) beans, insect-damaged beans, spotted (more than a quarter of a bean surface) beans, stinker and sour beans
<b>5. Robusta Parchment Bits</b>	
Sieve standard	100 percent by weight shall pass through a sieve with round holes of 5.00 mm (screen 13).
Garbling status	Ungarbled
May contain	Broken beans of less than 1/3 of a bean size, blacks/browns and defective beans of the prescribed size.

<b>6. Robusta Parchment Bulk</b>	
Grading	Ungraded
Presence of	Shall not contain more than
blacks/ Browns/ Bits	2 percent by weight
2) Unwashed Robusta - 'Robusta Cherry —	The grade designations of Robusta Cherry coffee are:
	i) Robusta cherry PB;
	ii) Robusta cherry AB;
	iii) Robusta cherry C;
	iv) Robusta cherry blacks/browns;
	v) Robusta cherry bits;
	vi) Robusta cherry bulk; and
	vii) Robusta cherry clean bulk.

**Quality Specifications**

<b>1. Robusta Cherry PB</b>	
Sieve standard	No sieve requirement
Garbling status	Clean garbled
Tolerance	
Flats (AB)	2 percent by weight
PB Triage	3 percent by weight
<b>2. Robusta Cherry AB</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.00 mm (screen 15). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 5.50 mm (screen 14).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	3 percent by weight
<b>3. Robusta Cherry C</b>	
Sieve standard	Minimum 75 percent by weight retention on a sieve with round holes of 5.50 mm (screen 14). 100 percent by weight shall stand on a sieve with round holes of 5.00 mm (screen 13).



**IS 3581 : 2019**

May include Triages small whole beans of the prescribed sieve size, light beans, boat shaped beans and spotted beans (less than a quarter of a bean surface). It shall not contain more than 2 percent of blacks/browns or bits.

**4. Robusta Cherry Blacks/Browns**

Sieve standard 100 percent by weight retention on a sieve with round holes of 5.00 mm (screen 13).

May include Black/dark brown beans, damaged beans such as bleached (spongy) beans, insect-damaged beans, spotted (more than a quarter of a bean surface) beans, fungal-damaged beans, sour and greens.

**5. Robusta Cherry Bits**

Sieve standard 100 percent by weight shall pass through a sieve with round holes of 5.00 mm (screen 13).

Garbling status Ungarbled

May contain Broken beans of less than 1/3 of a bean size, blacks/browns and defective beans of the prescribed size.

**6. Robusta Cherry Bulk**

Grading Ungraded

Presence of blacks/ browns/ bits Shall not contain more than 10 percent by weight

**7. Robusta Cherry Clean Bulk**

Grading Ungraded

Shall be free from Blacks/brown/bits

**4.2.2 Premium Grades**

a) Arabica coffee

1) Washed Arabica — ‘Plantation’

**Quality Specifications**

**1. Plantation AA**

Sieve standard Minimum 90 percent by weight retention on a sieve with round holes of 7.10mm (screen 18). 100 percent shall stand on a sieve with round holes of 6.65 mm (screen 17). The 10 percent beans passing through the sieve of 7.10 mm and standing on the sieve of 6.65mm shall be whole beans.

Garbling status Clean garbled

Tolerance

PB 2 percent by weight

**2. Plantation PB Bold**

Sieve standard 100 percent by weight retention on a sieve with oblong holes of 4.75 mm (screen 12 oblong).

Garbling status Clean garbled

Tolerance

AB 2 percent by weight

PB triage 2 percent by weight

2) Unwashed Arabica — ‘Arabica Cherry’

**Quality Specifications**

**1. Arabica Cherry AA**

Sieve Standard Minimum 90 percent by weight retention on a sieve with round holes of 7.10 mm (screen 18). 100 percent retention on a sieve with round holes of 6.65 mm (screen 17).

Garbling status Clean garbled

Tolerance

PB 2 percent by weight

Triage 1percent by weight



<b>2. Arabica Cherry A</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.65mm (screen 17). 100 percent by weight shall stand on a sieve with round holes of 6.00 mm (screen 15).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	2percent by weight

<b>3. Arabica Cherry PB Bold</b>	
Sieve standard	100 percent by weight retention on a sieve with oblong holes of 4.75 mm (screen 12 oblong).
Garbling status	Clean garbled
Tolerance	
AB	2 percent by weight
Triage	2 percent by weight

b) Robusta coffee

1) Washed Robusta — ‘Robusta Parchment’

**Quality Specifications**

<b>1. Robusta Parchment A</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.65 mm (screen 17). 100 percent shall stand on a sieve with round holes of 6.00 mm (screen 15).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	No tolerance

<b>2. Robusta Parchment PB Bold</b>	
Sieve standard	100 percent by weight retention on a sieve with oblong holes of 4.50 mm (screen 11 oblong).

Garbling status	Clean garbled
Tolerance	
AB	2 percent by weight
Triage	2 percent by weight

2) Unwashed Robusta — ‘Robusta Cherry’

**Quality Specifications**

<b>1. Robusta Cherry AA</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 7.10 mm (screen 18). 100 percent retention on a sieve with round holes of 6.65 mm (screen 17).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	1 percent by weight

<b>2. Robusta Cherry A</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.65 mm (screen 17). 100 percent by weight shall stand on a sieve with round holes of 6.00 mm (screen 15).
Garbling status	Clean garbled
Tolerance	
PB	2 percent by weight
Triage	2 percent by weight

<b>3. Robusta Cherry PB Bold</b>	
Sieve standard	100 percent by weight retention on a sieve with oblong holes of 4.50 mm (screen 11 oblong).
Garbling status	Clean garbled
Tolerance	
AB	2 percent by weight
PB Triage	2 percent by weight

**IS 3581 : 2019**

**5.3.3 Specialty Coffees**

a) Mysore nuggets extra bold

**Arabica Plantation (Washed Coffee)**

Region of growth Shall be prepared from plantation A coffees of Mysore, Coorg, Bababudan, Biligiris and Shevaroyes.

Sieve standard Minimum 90 percent retention on a sieve with round holes of 7.50 mm (screen 19). 100 percent retention on a sieve with round holes of 6.65 mm (screen 17). The 10 percent beans passing through the sieve of 7.50 mm and standing on the sieve of 6.65 mm shall be whole beans

Processing/garbling standard Medium to well-polished, clean garbled

Free from PB, broken (inclusive of Triage and Elephant beans) or any extraneous matter. Defectives including bleached and spongy beans, blacks, browns, insect damaged beans, fungal damaged beans and pulper cuts.

b) Robusta Kaapi Royale

**Robusta Parchment (Washed Coffee)**

Region of growth Shall be prepared from Robusta parchment AB coffee of Mysore, Coorg, Malabar, Wayanad, Shevaroyes, Pulneys and Bababudan regions.

Sieve standard Minimum 90 percent retention on a sieve with round holes of 6.70 mm (Screen 17). 100 percent retention on a sieve with round holes of 6.00 mm (screen 15). The 10 percent beans passing through the sieve of 6.70 mm and standing on the sieve of 6.00 mm shall be whole beans.

Processing/garbling standard Medium to well-polished, clean garbled

Free from PB, broken (inclusive of Triage and Elephant beans) or any extraneous matter. Defectives including bleached and spongy beans, unwashed beans, blacks, browns, insect damaged beans, fungal damaged beans and pulper cuts.

c) Monsooned Malabar coffees

1) *Monsooned Malabar Arabica Coffees (prepared from Arabica cherry coffee)* — The grade designations of Monsooned Malabar Arabica Coffees are:

- i) Monsooned Malabar AAA;
- ii) Monsooned Malabar AA;
- iii) Monsooned Malabar A; and
- iv) Monsooned Malabar Arabica Triage.

**1. Monsooned Malabar AAA**

Sieve standard Minimum 90 percent by weight retention on sieve with round holes of 7.50 mm (screen 19). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 7.10 mm (screen 18).

Garbling status Clean garbled

Tolerance

Triage Maximum 2 percent by weight

BBB Nil

**2. Monsooned Malabar AA**

Sieve standard Minimum 90 percent by weight retention on a sieve with round holes of 7.10 mm (screen 18). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 6.70 mm (Screen 1).

Garbling status Clean garbled

Tolerance

Triage Maximum 2 percent by weight

BBB Nil

<b>3. Monsooned Malabar A</b>	
Sieve standard	Minimum 75 percent by weight retention on a sieve with round holes of 6.70 mm (screen 17). Not more than 1.5 percent by weight shall pass through a sieve with round holes of 6.00 mm (screen 15).
Tolerance	
Triage	Maximum 3 percent by weight
BBB	Nil

<b>4. Monsooned Malabar Arabica Triage</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.00 mm (screen 15).
Tolerance	
BBB	3 percent

2) *Monsooned Malabar Robusta Coffees (Prepared from Robusta cherry coffee)*— The grade designations of Robusta Monsooned Malabar Coffees are:

- i) Monsooned Malabar Robusta RR; and
- ii) Monsooned Malabar Robusta Triage.

<b>1. Monsooned Malabar Robusta RR</b>	
Sieve standard	Minimum 90 percent by weight retention on sieve with round holes of 7.10 mm (screen 18). Not more than 1.5 percent by weight shall pass (screen 17).
Garbling status	Clean garbled
Tolerance	
Triage	Maximum 3 percent by weight
BBB	Nil

<b>2. Monsooned Malabar Robusta Triage</b>	
Sieve standard	Minimum 90 percent by weight retention on a sieve with round holes of 6.00 mm (screen 15).
Garbling status	Clean garbled
Tolerance	
BBB	3 percent

#### 5.3.4 Miscellaneous Grades

- 1. Liberica Bulk (Bulk coffee from Liberica)**

Grading	Ungraded
Presence of blacks, browns/ bits	Shall not contain more than 20 percent by weight.
- 2. Excelsia Bulk (Bulk coffee from Excelsia)**

Grading	Ungraded
Presence of blacks, browns/ bits	Shall not contain more than 20 percent by weight.

## 6 PACKING AND MARKING

### 6.1 Packing

The coffee beans shall be packed in new, clean and sound jute or lined bags or any other suitable container as agreed to between the purchaser and the vendor. The bags shall be free from any fungal or insect infestation and shall be free from any undesirable smell.

### 6.2 Marking

**6.2.1** The following particulars shall be marked or labelled on each bag:

- a) Name of the material;
- b) Variety and type;
- c) Grade of the material;
- d) Name and address of the vendor; and
- e) Net mass, in kg;
- f) Directions for storage; and
- g) Any other information required under the *Legal Metrology (Packaged Commodities) Rules, 2011*

**IS 3581 : 2019**

and the *Food Safety and Standards (Packaging and Labelling) Regulations, 2011* and the *Food Safety and Standards Act, 2006*.

**6.2.2 BIS Certification Marking**

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau*

*of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the standard mark.

**6.2.3** The product may also be marked with ECO Mark and the details are available with the Bureau of Indian Standards.

## ANNEX A

( Clause 4.1 )

### DETERMINATION OF MOISTURE

#### A-0 PRINCIPLE

Dry the sample of beans at a temperature of  $130 \pm 2^\circ\text{C}$ , at atmospheric pressure, in two stages with an intermediate rest period, in order to redistribute uniformly the moisture in the bean.

#### A-1 APPARATUS

##### A-1.1 Electrically Heated Constant — Temperature Oven

The oven shall have effective ventilation and shall be regulated in such a way that the temperature of the air and of the plates carrying the samples is  $130 \pm 2^\circ\text{C}$  in the vicinity of the samples. The oven shall have such heating capacity that when it is previously set at a temperature of  $130^\circ\text{C}$ , it is again able to reach this temperature in less than 45 min (preferably in less than 30 min) after the insertion of the maximum number of test portions that can be dried simultaneously.

##### A-1.2 Dish with Lid

This shall be of corrosion resistant metal or of glass, with an effective surface area of at least  $18\text{ cm}^2$  (for example, 50 mm minimum diameter and 25 to 30 mm deep).

##### A-1.3 Desiccator

Phosphorous pentoxide, reagent grade, or any other effective dehydrating agent shall be used in the desiccator.

##### A-1.4 Analytical Balance

#### A-2 PROCEDURE

##### A-2.1 Test Portion

Weigh the empty dried dish with its lid. Introduce approximately 5 g of green coffee beans and spread them over the bottom of the dish in a single layer. If the test portion contains a large quantity of impurities (nails, stones, wood, etc.) discard the test portion and take a fresh portion from the laboratory sample. Cover the dish with its lid and weigh the dish with lid and the test portion to the nearest 0.000 2 g.

##### A-2.2 Determination

###### A-2.2.1 First Period in the Oven

Place the dish containing the test portion in the oven at a temperature of the  $130^\circ\text{C}$ , on its lid. Remove it after a

period of  $6\text{ h} \pm 15\text{ min}$ ; cover it with the lid while still in oven and place it in the desiccator. After cooling to ambient temperature (from 30 to 40 min after placing it in the desiccator), weigh it, still closed. After weighing, replace the dish in the desiccator for at least 15 h.

###### A-2.2.2 Second Period in the Oven

Under the same conditions as specified in A-2.2.1, replace the dish in the oven at a temperature of  $130^\circ\text{C}$  and let it remain there for  $4\text{ h} \pm 15\text{ min}$ . Remove it, allow it to cool to ambient temperature in the desiccator and weigh again.

###### A-2.2.3 Number of Determinations

Carry out at least two determinations on the same sample till the difference in results of last two determinations is not more than 0.3 g of moisture per 100 g of the sample.

#### A-3 CALCULATION

A-3.1 The percentage of moisture in the sample shall be calculated by adding the percent loss in mass calculated after the first period in the oven (see A-2.2.1) and half the value of the addition percent loss in mass calculated after the second period in the oven (see A-2.2.2).

##### A-3.1.1 Loss in Mass after the First Period in Oven ( $P_1$ )

Calculate percent loss in mass using the following formula:

$$P_1 = \frac{(m_0 - m_1) \times 100}{m_0}$$

where,

$m_0$  = initial mass, in g of the test portion; and

$m_1$  = mass in g, of the test portion after the first 6 h period.

##### A-3.1.2 Loss in Mass after the second Period in Oven ( $P_2$ )

Calculate percent loss in mass using the following formula:

$$P_2 = \frac{(m_0 - m_2) \times 100}{m_0}$$

where,

$m_0$  = initial mass in g, of the test portion; and

$m_2$  = mass in g, of the test portion after the second 4 h period in the oven.

**IS 3581 : 2019**

**A-3.1.3 Moisture Content, Percent by Mass ( *P* )**

Calculate moisture content (percent by mass) using the following formula ( *see* Note ):

$$P = P_1 + \frac{P_2 - P_1}{2}$$

NOTE — The difference between the losses in mass observed after 6 h ( *see* A-2.2.1 ) and 10 h (including additional 4 h) ( *see* A-2.2.2 ) in the oven at a temperature of 130°C, that is, the difference between *P*<sub>1</sub> and *P*<sub>2</sub>, should normally be less than 1.0 g per 100 g of sample.





## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc No.: FAD 06 (13637).

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002  
Telephones: 2323 0131, 2323 3375, 2323 9402

Website: [www.bis.gov.in](http://www.bis.gov.in)

### Regional Offices:

	Telephones
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 2323 7617 2323 3841
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Kankurgachi KOLKATA 700054	{ 2337 8499, 2337 8561 2337 8626, 2337 9120
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg CHANDIGARH 160019	{ 265 0206 265 0290
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113	{ 2254 1216, 2254 1442 2254 2519, 2254 2315
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	{ 2832 9295, 2832 7858 2832 7891, 2832 7892

**Branches :** AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. COIMBATORE.  
DEHRADUN. DURGAPUR. FARIDABAD. GHAZIABAD. GUWAHATI.  
HYDERABAD. JAIPUR. JAMMU. JAMSHEDPUR. KOCHI. LUCKNOW.  
NAGPUR. PARWANOO. PATNA. PUNE. RAIPUR. RAJKOT. VISAKHAPATNAM.